

MAGNATECH

INTERNATIONAL BV

WWW.MAGNATECH-INTERNATIONAL.COM

T +31 321 38 66 77 | F +31 321 31 41 65
info@magnatech-international.com

“PARTNERSHIP IS
SHARING INFORMA-
TION. **THAT'S WHAT WE
DO** SHARING INFOR-
MATION & PROVIDING
SOLUTIONS”



MAGNATECH

VACUUM LIFTER



STANDARD PIPELIFTERS

TYPE BXH.	LIFTING CAPACITY (INCL. LARGE PAD)	SHIPPING WEIGHT (WITHOUT PAD)	DIMENSIONS NOMINAL (L x W x H) (WITHOUT PAD)
SC 75	7.500 kg 16.500 lb	625 kg 1.419 lb	2500 x 450 x 1400 mm 98,5" x 17,7" x 55" (inches)
SC 110	11.000 kg 24.230 lb	845 kg 1.860 lb	2500 x 450 x 1650 mm 98,5" x 17,7" x 65" (inches)
SC 150	15.000 kg 33.000 lb	1.030 kg 2.270 lb	2500 x 450 x 1700 mm 98,5" x 17,7" x 67" (inches)

LIFTER

CAPACITY:	up to 15,000 KGS
ENGINE TYPE/MODEL:	Yanmar Diesel, model L48
FEATURES:	<ul style="list-style-type: none"> Wireless radio remote controls Wireless radio remote in-cab alarm feedback Self-contained Optional flip-up legs Hydraulic rotating top-end for use with excavator Rotating torque 3.3 kNm Lifting lugs for use with crane
STANDARDS ADOPTED:	98/37/EC, 73/23/EEG, 89/336/EEG, EN292-1+2, EN294, EN349, EN418, EN1050, EN60204, ASME B30.20a-2001

SUCTION PADS

SIZE RANGE:	4" pipe - ∞ (flat plate on request)
FEATURES:	<ul style="list-style-type: none"> Spring loaded guide wheels Replaceable rubber seal Quick fittings
APPLICATION:	Coated/non-coated pipe (except concrete coated pipe)

